


BL neonVIEW

Diffused, Flexible, Linear LED Lighting
Flat or Dome Profile, 120VAC

LINE Series

Printed



Certification



Lighting



Lamp	LED, SMD 5050, 27 Diodes/FT (84 Diodes/m)
Load	1.83 W/FT (6 W/m)
Beam Angle	160° (Flat), 270° (Dome)
Average Life	50,000 Hours
Lumens	9 - 76 lm/FT
Efficacy	5 - 42 lm/W

Electrical

Control	Wireless Plug-in lamp dimmer with remote
Input Voltage	120VAC
Connections	Male Plug-in Style
Operating Temperature	-4°F to 104°F (-20°C to 40°C)

Mechanical

Housing Construction	Injection Moulded White PVC
Cutting Increments	19.7" (50 cm)
Maximum Run Length	65' (20M)
Medial Bend Radius	2.36" (60mm)
Environmental	IP65
Mounting	Clip, Track

Accessories

BL neonVIEW LINE TK	Termination Kit, Factory Installed
BL neonVIEW LINE JC	Jumper Cable, Factory Installed

PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the
BL LIGHTING catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

bllighting.com



BL neonVIEW

Diffused, Flexible, Linear LED Lighting
Flat or Dome Profile, 120VAC

LINE Series

Printed

Performance

Dome Profile	CCT/Color	Load	Lumens	Efficacy
	2700K	1.83 W/FT	76 lm/FT	42 lm/W
	3000K	1.83 W/FT	76 lm/FT	42 lm/W
	4000K	1.83 W/FT	76 lm/FT	42 lm/W
	5700K	1.83 W/FT	76 lm/FT	42 lm/W
	Red	1.83 W/FT	27 lm/FT	15 lm/W
	Green	1.83 W/FT	76 lm/FT	42 lm/W
	Blue	1.83 W/FT	12 lm/FT	7 lm/W
	Amber	1.83 W/FT	27 lm/FT	15 lm/W
Flat Profile	CCT/Color	Load	Lumens	Efficacy
	2700K	1.83 W/FT	61 lm/FT	33 lm/W
	3000K	1.83 W/FT	61 lm/FT	33 lm/W
	4000K	1.83 W/FT	61 lm/FT	33 lm/W
	5700K	1.83 W/FT	61 lm/FT	33 lm/W
	Red	1.83 W/FT	23 lm/FT	9 lm/W
	Green	1.83 W/FT	61 lm/FT	33 lm/W
	Blue	1.83 W/FT	9 lm/FT	5 lm/W
	Amber	1.83 W/FT	23 lm/FT	13 lm/W

Ordering

Series

BL neonVIEW LINE

Profile

DM = Dome
FT = Flat

CCT/Color

27 = 2700K
30 = 3000K
40 = 4000K
57 = 5700K
RD = Red
GN = Green
BE = Blue
AR = Amber

Ingress Protection

65 = IP65

PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the
BL LIGHTING catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

bllighting.com



BL neonVIEW


Diffused, Flexible, Linear LED Lighting
Flat or Dome Profile, 120VAC

LINE Series


Printed

Dimensions

Dome Profile Part# LINETK



Flat Profile Part# LINETK



PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the
BL LIGHTING catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

bllighting.com

