

BL CBOX 10V

Fully Assembled Control + Power Boxes Dual Circuit, 100W, 24VDC, CV, 0-10V

AE10010BCL

Printed	
THILEG	



Certification







Electrical

Input Voltage 120V - 277VAC Input Frequency 60 Hz Max Input Current

(x2) 2A (x2) 24VDC, 4.1A, Constant Voltage (x2) 100W Output Voltage Load

Connections

18 AWG, Copper Conductors 20% - 25% Min Load

Power Factor 0.9

-30°C to 60°C Operating Temperature Class 2 Circuit Control 0-10V

Mechanical

Enclosure Construction PVC.

High Temperature Flame-Proof Plastic

Certificate

UL2108, UL 1598/CSA 250.0, UL 8750, CSA 250.13

Weight Environmental Assembly

IP66, NEMA 1, 2, 3R, 4, 4X, 6, 6P, 12, 13

PVC Enclosure (x2) LED Driver Carbon Steel Back-Plate Surge Protector Strain Relief (Set)


Electrical Connectors (Set)

PROJECT CLIENT TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the **BL LIGHTING** catalogue










	10V


Fully Assembled Control + Power Boxes Dual Circuit, 100W, 24VDC, CV, 0-10V

AE10010BCL

Printed	

Dimensions





PROJECT

CLIENT

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the **BL LIGHTING** catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

III - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

