BL flexFORM LINE D1

Flexible, Linear LED Strip Lighting Monochromatic, Line Voltage



Continuous run lengths up to 150FT are achievable on a single plug, with our flexible,120V LED ribbon. Perfect for architectural accents and certified for indoor and outdoor use, easily add highlights to soffits, coves, under cabinets, bar shelving and displays, in commercial, residential, and retail environments. BL flexFORM LINE D1 produces a uniform 146 lm/FT, is simple to install with mounting clips or channel, and UL listed, custom lengths ship within 1-2 days!

Up to 130 lm/ft

150ft on a single plug

Quick Ship

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail












	Number of LED's	18 Diodes/FT (60/m)
Lighting	Lamp	SMD 5050
	Beam Angle	120°
	Average Life	30,000 Hours
	CCT Binning	SDCM <3 LED's
Electrical	Input Voltage	120VAC
	Connections	Male Socket Plugin
Mechanical	Housing Construction	Flexible PCB Board, PVC Jacket
	Mounting Options	Clips, PVC Channel, Adhesive
Environmental	Ingress Protection	IP65
	Certifications	ETL
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)

Performance

CCT/Color		3000К	4000К	
Power	W/FT (W/m)	2.5(8.2)		
Lumens	Im/FT (Im/m)	120 (394)	130 (427)	
Efficacy	lm/W	48	52	
CRI	CRI	90		
Increment	inch (mm)	17.72 (450)		
Max. Length	ft (m)	150ft (45.7m)		

Ordering



Dimensions



	Section		Α	В	С	D
			inch (mm)			
		DMP(IP65)	0.56 (14.5)	17.72 (450)	5ft(1.5m)	0.31 (8)

BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.





