

Integrating highly controllable RGB and true white CCT diodes into a single, dynamic chip, our flexible RGBW LED strip is perfect for architectural accenting, and certified for indoor and outdoor use. Add color changing effects to coves, under cabinets, bar shelving, and displays, in commercial, residential, and retail environments. BL flexFORM RGBW is compatible with BL fixFORM Profiles, and UL listed, custom lengths ship within 1-2 days!

Up to 171 lm/ft

4.5W/FT

90+ CRI

Quick Ship

|              |  |
|--------------|--|
| CLIENT       |  |
| PROJECT NAME |  |
| LOCATION     |  |
| DATE         |  |

Product Detail



|               |                       |                                     |
|---------------|-----------------------|-------------------------------------|
| Lighting      | Number of LED's       | 18 Diodes/FT (60/m)                 |
|               | Lamp                  | SMD 5050                            |
|               | Beam Angle            | 120°                                |
|               | Average Life          | 50,000 Hours                        |
| Electrical    | CCT Binning           | SDCM <3 LED's                       |
|               | Controls              | DMX, Bluetooth                      |
|               | Input Voltage         | 24VDC                               |
|               | Max Input Current     | 5A                                  |
| Mechanical    | Connections           | 20AWG, Copper Conductors            |
|               | Circuit               | Class 2                             |
|               | Housing Construction  | Flexible PCB Board, Silicone Jacket |
|               | Mounting Options      | Clips, Channel, Adhesive            |
| Environmental | Ingress Protection    | IP65                                |
|               | Certifications        | cULus, CE, RoHS Compliant           |
|               | Operating Temperature | -4°F to 104°F (-20°C to 40°C)       |


Performance

| CCT/Color   |              | RGBW (3000K)    |
|-------------|--------------|-----------------|
| Power       | W/FT (W/m)   | 4.5(14.8)       |
| Lumens      | lm/FT (lm/m) | 171 (561)       |
| Efficacy    | lm/W         | 38              |
| CRI         | CRI          | 90+             |
| Increment   | inch (mm)    | 3 - 15/16 (100) |
| Max. Length | ft (m)       | 20ft (6.1m)     |

Ordering

|                  |             |           |         |
|------------------|-------------|-----------|---------|
| Product Code     | Color       | IP Rating | Profile |
| BL flexFORM RGBW | RGBW(3000K) | IP65      |         |

Dimensions



| Section |           | A         | B          | C         | D          |
|---------|-----------|-----------|------------|-----------|------------|
|         |           | inch (mm) |            |           |            |
|         | DMP(IP65) | 0.47 (12) | 3.93 (100) | 5ft(1.5m) | 0.19 (4.8) |



## Compatible Profile

Measurements in inch (mm)

Dotting Table:

**A** = No visible dots

**B** = Slight visible dots

**C** = Clear visible dots



### Surface Mount

|  |   |  |                     |                            |
|--|---|--|---------------------|----------------------------|
|  | BL fixFORM<br><b>SF Channel</b>   |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Square</b>  |  | Dotting<br><b>B</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Rectangle</b>   |  | Dotting<br><b>A</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Round</b>   |  | Dotting<br><b>B</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Shallow 1709</b>                                      |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Focus Beam</b><br>30° Beam Spread Lens Optic          |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Single Side 45</b><br>45° Angle Frosted Optic         |  | Dotting<br><b>B</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>SF Double Side 45</b><br>Double Sided Frosted Lens Optic |  | Dotting<br><b>B</b> | <a href="#">Spec Sheet</a> |

### Recessed Mount

|  |   |  |                     |                            |
|--|---|--|---------------------|----------------------------|
|  | BL fixFORM<br><b>Recessed 2626</b><br>In-Floor Profile                |  | Dotting<br><b>A</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>Recessed Shallow 2811</b><br>3/8" Recess Depth       |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>Recessed 4435</b><br>Ceiling Flanged Extrusion       |  | Dotting<br><b>A</b> | <a href="#">Spec Sheet</a> |
|  | BL fixFORM<br><b>Recessed Trimless 2414</b><br>Mud-In Drywall Channel |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |

### Stair Nose

|  |                                 |  |                     |                            |
|--|---------------------------------|--|---------------------|----------------------------|
|  | BL fixFORM<br><b>Stair Nose</b> |  | Dotting<br><b>C</b> | <a href="#">Spec Sheet</a> |
|--|---------------------------------|--|---------------------|----------------------------|

