

SPECIFICATIONS - A01 -

BL CBOX 10V

Fully Assembled Control + Power Boxes Dual Circuit, 75W, 24VDC, CV, 0-10V

FH7510BCL

Printed



Certification



Electrical

Input Voltage Input Frequency Max Input Current Output Voltage Load Connections Min Load Power Factor Operating Temperature Circuit Control

120V - 277VAC 60 Hz (x2) 2A (x2) 24VDC, 3.125A, Constant Voltage (x2) 75W 18 AWG, Copper Conductors 20% - 25% 0.9 -30°C to 60°C Class 2 0-10V

Mechanical

Enclosure Construction	PVC High Temperature Flame-Proof Plastic
Certificate	UL2108, UL 1598/CSA 250.0, UL 8750, CSA 250.13
Weight Environmental Assembly	IP66, NEMA 1, 2, 3R, 4, 4X, 6, 6P, 12, 13 PVC Enclosure (x2) LED Driver Carbon Steel Back-Plate Surge Protector Strain Relief (Set) Electrical Connectors (Set)

PROJECT CLIENT TYPE Solid State Lighting is sensitive to power fluctuations Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure Lack of surge protection may void your warranty For more information, please download the **BL LIGHTING** catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 358
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.





SPECIFICATIONS - A02 -


BL CBOX 10V

Fully Assembled Control + Power Boxes Dual Circuit, 75W, 24VDC, CV, 0-10V

FH7510BCL

Printed

Dimensions





PROJECT	CLIENT	ТҮРЕ	
Solid State Lighting is sensitive to power fluctuations Surge protection is highly recommended for all LED lightir Lack of surge protection may void your warranty	ng products and should be on a designated circuit to protect against premature failu	For more information, please download BL LIGHTING catalogue	d the
BL LIGHTING. ILLUMINATE EVERYTHING III – 8838 Heather St. Vancouver, BC. Canada. V6 P: 1-604-874-4405 F: 1-604-321-0445 E: info@b Copyright © 2017 BL INNOVATIVE LIGHTING. All Righ		bllighting.com	