


SPECIFICATIONS - A01 -

BL CBOX MLV

Fully Assembled Control + Power Boxes Single Circuit, 96W, 24VDC, CV, Phase Cut

MG96AM

Printed



Certification



Electrical

Control Input Voltage Input Frequency Max Input Current Output Voltage Load Max Current Connections Min Load **Power Factor** Operating Temperature Circuit Min. Dimming Level

MLV/Standard/Triac 120VAC 50/60 Hz 1A 24VDC, Constant Voltage 96W 4A 14 AWG, Copper Conductors 8W 0.95 -30°C to 50°C Class 2 25%

Mechanical

Enclosure Construction PVC

Certificate

Weight Environmental Assembly

High Temperature Flame-Proof Plastic

UL2108, UL 1598/CSA 250.0, UL 8750, CSA 250.13

IP66, NEMA 1, 2, 3R, 4, 4X, 6, 6P, 12, 13 **PVC Enclosure** LED Driver Carbon Steel Back-Plate Surge Protector Strain Relief (Set) Electrical Connectors (Set)

PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure Lack of surge protection may void your warranty

For more information, please download the **BL LIGHTING** catalogue

BL LIGHTING. ILLUMINATE EVERYTHING


III - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.






BL CBOX MLV MG96AM Printed Fully Assembled Control + Power Boxes Single Circuit, 96W, 24VDC, CV, Phase Cut MG96AM Printed

Dimensions





PROJECT	CLIENT	ТҮРЕ	
Solid State Lighting is sensitive Surge protection is highly reco Lack of surge protection may	mmended for all LED lighting products and should be on a designated circuit to protect against premature failure	For more information, please do BL LIGHTING catalogue	wnload the
P: 1-604-874-4405 F: 1-6	: EVERYTHING ncouver, BC. Canada. V6P 3S8 304-321-0445 E: info@bllighting.com DVATIVE LIGHTING. All Rights Reserved.	bllighting.com	

SPECIFICATIONS - A02 -