

BL inGROUND

Circular, Outdoor Recessed Luminaire
2.5W, 24VDC Constant Voltage

DISK 070


Printed



Certification



Lighting



Lamp	SMD3030 LED
CRI	73
Power	2.7 W/Unit
Average Life	50,000 Hours
Lumens	6 lm/Unit
Efficacy	2.2 lm/W

Electrical

Control	0-10V, MLV, ELV, Phase-Cut, Triac, DMX, Bluetooth
Input Voltage	24VDC
Connections	16AWG, Copper Conductors
Power Cable Length	20" (50cm)
Operating Temperature	-4°F to 104°F (-20°C to 40°C)

Mechanical

Environmental	IP67
Housing	Powder coated aluminum
Front Cover	316 stainless steel
Diameter Front Cover	2.76" (70 mm)
Gasket	Silicone seal
Mounting Sleeve	ABS Plastic
Weight	Sleeve = 0.22 lb (0.1kg) Luminaire = 0.88 lb (0.4kg)
Weight Bearing	4409lbs (2000 kg)
Impact Protection Rating	IK10
Lens	Optic Lens

PROJECT

CLIENT

TYPE



BL inGROUND

Circular, Outdoor Recessed Luminaire
2.5W, 24VDC Constant Voltage

DISK 070

Printed

Performance

CCT	Power (Unit)	Lumens (Unit)
2000K	2.7 W	6 lm
3000K	2.7 W	6 lm
4000K	2.7 W	6 lm
6000K	2.7 W	6 lm

Ordering

Series	CCT	Style of the cap
BL inGROUND DISK 070	<input type="text"/>	<input type="text"/>
	20 = 2000K 30 = 3000K 40 = 4000K 60 = 6000K	1S = 1 slot 2S = 2 slots 4S = 4 slots

Dimensions

