

BL Controls AKD node is a 4 Universe passive network device used to convert Artnet data from an Ethernet network to DMX512, simplifying cable runs and reducing the need for excess DMX distribution hardware. Supports individually configurable DMX512 In/Out on each channel along with Art-Net and sACN protocols. Deliver DMX pixel mapping programs to your luminaires to create dynamic lighting effects and take charge of your color changing and pixel control!

Up to 4 universes

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Details



Power Input	802.3af Power over Ethernet. Maximum power budget 8W
Weight	0.49kg
Connections	1 RJ45 and 4 x 3 pin XLR
IP Rating	IP20
Certificates	CE, FCC



Features & Benefits

- Internal DMX512-A line biasing termination as per ANSI E1.20 RDM requirements
- Ethernet 10/100Mbps Auto MDI-X port
- Art-Net, Art-Net II, Art-Net 3, Art-Net 4 and sACN/E1.31 support
- ANSI E1.20 RDM compliant with RDM over Art-Net
- Universe Sync Art-Net, sACN and Madrix Post Sync
- Both HTP and LTP merging of 2 Art-Net/sACN streams per port
- sACN Priority
- Internal merging capability with DMX In and DMX Out ports on same Universe
- IPv4 Addressing
- IGMPv2 for multicast network management
- DMX512 Frame Rate: Adjustable per port
- DMX512 Port Protection: DMX512-A Protected as per E1.11-2008

Ordering

Product Code	Universes	Power	IP Rating
AKD	4U	POE	IP20

Dimensions

