

BL Wall FS48

Outdoor Recessed Wall Light
3W, 120-240VAC Input




BL Wall FS48 recessed wall lights are built to blend seamlessly into the landscape, and ideal for stairway and pathway lighting. Available in 2000K, 3000K or 6000K CCT options. The unit is durably constructed with a die-cast aluminum body and front plate while the stainless steel mounting sleeve allows uniform and fast installations. Low profile and efficient, these luminaires are IP65 outdoor rated.

Up to 39 lm/unit 120-240VAC Input

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	LED	SMD 3030
	Power	3W
	Average Life	50,000 Hours
Electrical	Controls	Dali, PWM, Triac, 1-10V
	Input Voltage	120-240VAC
	Operating Current (MA)	48
Mechanical	Housing Construction	Dark Grey Powder Coated Aluminum
	Front Cover	Dark Grey Powder Coated Aluminum
	Mounting Sleeve	Stainless Steel
	Power Cable	3-Core 18AWG, Length = 1.6FT (0.5m)
Environmental	Ingress Protection	IP65
	Certifications	ETL, CE, RoHS Compliant
	Impact Protection	IK10
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)

Performance

Power	W/unit	3		
CCT	CCT	2000K	3000K	6000K
Lumens	lm/unit	33	36	39
Efficacy	lm/W	11	12	13
CRI	CRI	70	80	70

Ordering

Product Code	CCT	Finish
BL Wall FS48		
	2000K	DG (Dark Grey -Standard)
	3000K	SG (Silver Grey)
	6000K	BK (Black)

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 E: info@blighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at blighting.com for current technical data.


For more information, please download the BL LIGHTING catalog

blighting.com




Dimensions

FS48




Recessed Mounting Sleeve



Photometric Details

Illuminance



Light Distribution

