

BL fiberSOURCE Mira is an efficient 18W LED illuminator, emitting a bright 3000K or 4000K white light output of 1820 lm. With a low profile and compact body measuring just 8.75"x4.5"x3.2" BL fiberSOURCE Mira fits easily into small and narrow spaces, and can be dimmed manually or with 010V or DMX protocols. Perfect for small projects, niche accents, and BL fiberOPTIC Starfields.

Up to 1820lm Output

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	CCT	3000K, 4000K
	Average Life	36,000 Hours
Electrical	Controls	DMX, 0-10V, Switch
	Input Voltage	90V-264VAC
	PSU Output	24VDC
	Temp. Range	14°F to 113°F (-10°C to 45°C)
Mechanical	Housing Construction	ABS
	Environmental	IP20
	Aperture Diameter	1-3/16" (30mm)
	Weight	2.03b (920g)

Performance

CCT/Color		3000K	4000K
Power	W/unit	18W	
Lumens	lm/unit	1770	1820
Efficacy	lm/W	98	101
CRI		80	

Ordering

Product Code	CCT/Color	Control
BL fiberSOURCE Mira		
	3000K	NO (No Dimming)
	4000K	010V DMX

Dimensions

