BL fiberSOURCE Pavo

LED Light Engine Designed for BL fiberOPTIC 93W RGBW DMX



BL fiberSOURCE PAVO is a high performance, DMX enabled, RGBW LED illuminator, designed to integrate with BL fiberOPTIC, to create vibrant, rich, color changing and optional twinkling effects. The 93W RGBW LED may be ordered in 6500K, 4000K or 3000K, and has a 50,000 hour lamp life. Take charge of your color changing, dimming and twinkling effects with DMX control, or optional RF Remote. Perfect for custom chandeliers, decorative accenting, color changing starfield ceilings, and creating fun, activated illuminated displays.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Powerful RGBW Illuminator

8010lm Output

DMX Controlled

Product Detail












Lighting	Power	93W
	Average Life	50,000 Hours
Electrical	Controls	DMX, RF Remote, Switch
	Input Voltage	100V-240VAC
	Temp. Range	14°F to 113°F (-10°C to 45°C)
Mechanical	Housing Construction	Sheet steel
	Finish	Powdercoat grey
	Wheel Options	Twinkle Wheel
	Environmental	IP20
	Aperture Diameter	1-3/16" (30mm)
	Certification	UL


Performance

CCT/Color		RGBW (3000K)	RGBW (4000K)	RGBW (6500K)
Power	W/unit		93W	
Lumens	Im/unit	8010		
Efficacy	Im/W		86	

Ordering



Dimensions



BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information BL LIGHTING catalog

bllighting.com



145

[5.70"]