# **BL fiberSOURCE Petra**




BL fiberSOURCE Petra is a powerful 90W LED illuminator, emitting up to 5700 lm, rivaling the brilliant light output of less efficient metal halide lamps, and capable of illuminating long runs of BL fiberOPTIC, perfect for architectural accenting. The white light LED has an average 36,000 hour lamp life, and can be specified in a wide range of Kelvin temperatures, from warm 3000K to a cool 5500K, and can be fitted with either a 6-Color Wheel, or Twinkle Wheel, for special effects. Options available for easy control of your dimming, color changing, or twinkling effects, include a built in manual dimmer, 010V or DMX protocols.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

#### Up to 5700lm Output

## **Product Detail**




#### Performance

CCT/Color		3000K	4000K	5500K
Power	W/unit		90W	
Lumens	lm/unit	4650	5300	5700
Efficacy	lm/W	52	53	63
CRI		83	82	76

## Ordering

Product Code	CCT/Color	Control	Effect			
BL fiberSOURCE Petra		_				
	3000K	NO (No Dimming)	NO (No Wheel)			
	4000K	010V	CW (Color Wheel)			
	5500K	DMX	TW (Twinkle Wheel)			

#### Dimensions



# BL LIGHTING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty. Designed & Assembled in North America.

For more information please downlad the BL LIGHTING catalog



Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

bllighting.com

1