

BL fixFORM SPK Suspended allows you to design your own custom pendant luminaire. The compatible aluminum extruded channels are available with your choice of diffuser lens profiles, and integrates with BL flexFORM LED to offer a wide range of lumen packages, Kelvin temperatures, and dimming options. Conductive suspension wires combine structural with electrical to seamlessly energize the light, and are adjustable in height. Each module may be custom pre-assembled to any length from 6" to 6'-0", allowing you to uniformly illuminate your space with energy efficient light.

**Adjustable height**

<b>CLIENT</b>	
<b>PROJECT NAME</b>	
<b>LOCATION</b>	
<b>DATE</b>	

## Product Detail



<b>Electrical</b>	Size	18 AWG
	Rated Voltage	300V
	Max. Input Current	8A
	Operating Temperature	194°F (90°C)
	Conductor Material	Tinned Copper Conductor
<b>Mechanical</b>	Housing Construction	Anodized Aluminium Hangers, Hex Bolt Fastener
	Cable Length	(x2) 6ft(1.83m)
	Jacket Material	PVC
	Jacket Thickness	0.45mm
	Jacket Diameter	2.7mm
	Insulation Material	FEP
	Insulation Thickness	0.31mm
<b>Environmental</b>	Insulation Diameter	1.52mm
	Ingress Protection	IP20
	Certifications	cULus



## Ordering

<b>Product Code</b>
BL fixFORM SPK

## Dimensions

