

Delivering an ultra bright 800 lm/FT, our flexible, dimmable, LED strip is vivid enough for general illumination, and certified for indoor and outdoor use. Add architectural accents to coves, under cabinets, bar shelving, and displays, in commercial, residential, and retail environments. Available in IP20 or IP65 rated for wet locations, BL flexFORM D4 is compatible with BL fixFORM Profiles, and UL listed, custom lengths ship within 1-2 days!

Up to 800 lm/ft

8W/FT

90+ CRI

Quick Ship

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



IP20

IP65

LOW

DIM

Bluetooth

CE

RoHS

LISTED

5 YEAR WARRANTY

Lighting	Number of LED's	30 Diodes/FT (98/m)
	Lamp	LG 5630
	Beam Angle	150°
	Average Life	50,000 Hours
Electrical	CCT Binning	SDCM <3 LED's
	Controls	0-10V, MLV, ELV, Phase-Cut, Triac, DMX, Bluetooth
	Input Voltage	24VDC
	Max Input Current	5.5A
Mechanical	Connections	20AWG, Copper Conductors
	Circuit	Class 2
	Housing Construction	Flexible PCB Board, Silicone Jacket
Environmental	Mounting Options	Channel
	Ingress Protection	IP20, IP65
	Certifications	cULus, CE, RoHS Compliant
Operating Temperature	-4°F to 104°F (-20°C to 40°C)	

Performance

CCT/Color		3000K	3500K	4000K
Power	W/FT (W/m)	8(26.2)		
Lumens	lm/FT (lm/m)	800 (2,625)	800 (2,625)	800 (2,625)
Efficacy	lm/W	96	96	96
CRI	CRI	90+		
Increment	inch (mm)	2.75 (70)		
Max. Length	ft (m)	11ft (3.35m)		

Ordering

Product Code	CCT	IP Rating	Profile
BL flexFORM D4			
	3000K	IP20	
	3500K	IP65	
	4000K		

Dimensions

A Width

B Increment

C End Cap (IP65 only)

D Height

Section		A	B	C	D
		inch (mm)			
	DRY(IP20)	0.50 (12)	2.75 (70)	-	0.05 (1.3)
	DMP(IP65)	0.56 (14)	2.75 (70)	0.63 (16)	0.22 (5.5)

Compatible Profile

- Compatibility chart is for DRY (IP20) tape only
- Measurements in inch (mm)

Dotting Table:

A = No visible dots

B = Slight visible dots

C = Clear visible dots



Surface Mount

	BL fixFORM SF Channel 2212		Dotting C	Spec Sheet
	BL fixFORM SF Square 2222		Dotting A	Spec Sheet
	BL fixFORM SF Rectangle 2232		Dotting A	Spec Sheet
	BL fixFORM SF Round 2221		Dotting A	Spec Sheet
	BL fixFORM SF Shallow 1709		Dotting B	Spec Sheet
	BL fixFORM SF Square 1617		Dotting A	Spec Sheet
	BL fixFORM SF Wide 4930 Requires 2 LED Strips		Dotting A	Spec Sheet
	BL fixFORM SF Focus Beam 30° Beam Spread Lens Optic		Dotting C	Spec Sheet

Recessed Mount

	BL fixFORM Recessed 2626 In-Floor Profile		Dotting A	Spec Sheet
	BL fixFORM Recessed Shallow 2811 3/8" Recess Depth		Dotting B	Spec Sheet
	BL fixFORM Recessed 2416 Ceiling Flanged Extrusion		Dotting A	Spec Sheet
	BL fixFORM Recessed 4435 Ceiling Flanged Extrusion		Dotting A	Spec Sheet
	BL fixFORM Recessed Trimless 2414 Mud-In Drywall Channel		Dotting B	Spec Sheet

Specialty

	BL fixFORM SF Contour 1905 Bendable LED Channel		Dotting C	Spec Sheet
	BL fixFORM Stair Nose		Dotting B	Spec Sheet

Suspended

	BL fixFORM SP Round 2020 Suspended and Surface Mount Options Available		Dotting A	Spec Sheet
--	---	--	---------------------	----------------------------

