

BL flexFORM D6

Flexible, Linear LED Strip Lighting
Monochromatic, 24VDC, Constant Voltage



Delivering up to 678lm/FT, our flexible, dimmable, high lumen output LED ribbon is perfect for architectural highlighting, and certified for indoor and outdoor use. Add energy efficient accents to coves, under cabinets, bar shelving, and displays, in commercial, residential, and retail environments. Available in IP20 or IP65 rated for wet locations, BL flexFORM D6 is compatible with BL fixFORM Profiles, and UL listed, custom lengths typically ship within 1-2 days!

Up to 678 lm/ft


5.85W/FT

97+ CRI

Quick Ship

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	Number of LED's	48 Diodes/FT (157/m)
	Lamp	SMD 2835
	Beam Angle	120°
Electrical	Average Life	50,000 Hours
	CCT Binning	SDCM <3 LED's
	Controls	0-10V, MLV, ELV, Phase-Cut, Triac, DMX, Bluetooth
	Input Voltage	24VDC
	Max Input Current	5A
Mechanical	Connections	20AWG, Copper Conductors
	Circuit	Class 2
	Housing Construction	Flexible PCB Board, Silicone Jacket
Environmental	Mounting Options	Channel
	Ingress Protection	IP20, IP65
	Certifications	cULus, CE, RoHS Compliant
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)


Performance

CCT/Color		2700K	3000K	3500K	4000K
Power	W/FT (W/m)	5.85 (19.2)			
Lumens	lm/FT (lm/m)	632 (2,074)	643 (2,112)	643 (2,112)	678 (2,227)
Efficacy	lm/W	108	109	109	115
CRI	CRI	97+			
Increment	inch (mm)	1.96 (50)			
Max. Length	ft (m)	15ft (4.57m)			

Ordering

Product Code	CCT	IP Rating	Profile
BL flexFORM D6	2700K	IP20	
	3000K	IP65	
	3500K		
	4000K		

Dimensions



Section		A	B	C	D
		inch (mm)			
	DRY(IP20)	0.39 (10)	1.96 (50)	-	0.06 (1.6)
	DMP(IP65)	0.57 (14.5)	1.96 (50)	0.63 (16)	0.24 (6)

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com



Compatible Profile

- Compatibility chart is for DRY (IP20) tape only
- Measurements in inch (mm)

Dotting Table:

A = No visible dots

B = Slight visible dots

C = Clear visible dots



Surface Mount

	BL flexFORM SF Channel 2212	 0.77 (19.5) x 0.44 (11.2)	Dotting C	Spec Sheet
	BL flexFORM SF Square 2222	 0.77 (19.5) x 0.78 (19.8)	Dotting A	Spec Sheet
	BL flexFORM SF Rectangle 2232	 0.77 (19.5) x 1.20 (30.4)	Dotting A	Spec Sheet
	BL flexFORM SF Round 2221	 0.77 (19.5) x 0.77 (19.5)	Dotting A	Spec Sheet
	BL flexFORM SF Shallow 1709	 0.68 (17.4) x 0.32 (8.2)	Dotting A	Spec Sheet
	BL flexFORM SF Square 1617	 0.69 (17.5) x 0.63 (16)	Dotting A	Spec Sheet
	BL flexFORM SF Wide 4930 Requires 2 LED Strips	 1.97 (50) x 1.26 (32)	Dotting A	Spec Sheet
	BL flexFORM SF Focus Beam 30° Beam Spread Lens Optic	 0.77 (19.5) x 0.66 (16.6)	Dotting C	Spec Sheet

Recessed Mount

	BL flexFORM Recessed 2626 In-Floor Profile	 1.02 (26) x 1.02 (26)	Dotting A	Spec Sheet
	BL flexFORM Recessed Shallow 2811 3/8" Recess Depth	 1.10 (28.1) x 0.92 (23.5)	Dotting B	Spec Sheet
	BL flexFORM Recessed 2416 Ceiling Flanged Extrusion	 0.95 (24) x 0.69 (17.5)	Dotting B	Spec Sheet
	BL flexFORM Recessed 4435 Ceiling Flanged Extrusion	 1.73 (44) x 1.38 (35)	Dotting A	Spec Sheet
	BL flexFORM Recessed Trimless 2414 Mud-In Drywall Channel	 2.82 (71.6) x 1.24 (31.6)	Dotting C	Spec Sheet

Specialty

	BL flexFORM SF Contour 1905 Bendable LED Channel	 0.71 (18) x 0.35 (9)	Dotting C	Spec Sheet
	BL flexFORM Stair Nose	 2.32 (59.1) x 0.65 (16.7)	Dotting B	Spec Sheet

Suspended

	BL flexFORM SP Round 2020 Suspended and Surface Mount Options Available	 0.79 (20) x 0.79 (20)	Dotting B	Spec Sheet
--	--	---------------------------	---------------------	----------------------------

