

BL flexFORM Premium Cut D3

Flexible, Linear LED Strip Lighting
Monochromatic, 24VDC, Constant Voltage



Delivering up to 470lm/FT, our flexible, dimmable, high lumen output LED ribbon is perfect for architectural highlighting, and certified for indoor and outdoor use. Cuttable every 0.33" (8.33mm), BL flexFORM Premium Cut D3 allows for exact custom run lengths. Add energy efficient accents to coves, under cabinets, bar shelving, and displays, in commercial, residential, and retail environments. Available in IP20 or IP65 rated for wet locations, BL flexFORM Premium Cut D3 is compatible with BL fixFORM Profiles, and UL listed, custom lengths typically ship within 1-2 days!

- 0.33" (8.33mm) Increments
- Up to 470 lm/ft
- 4.4W/FT
- 90+ CRI
- Quick Ship

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



<div>IP20</div> <div>IP65</div> <div>LOW</div> <div>DIM</div> <div>Bluetooth</div>	Lighting	Number of LED's	37 Diodes/FT (120/m)
		Lamp	SMD 2835
		Beam Angle	120°
		Average Life	50,000 Hours
		CCT Binning	SDCM <3 LED's
<div>CE</div> <div>RoHS</div> <div>UL LISTED</div> <div>5 YEAR WARRANTY</div>	Electrical	Controls	0-10V, MLV, ELV, Phase-Cut, Triac, DMX, Bluetooth
		Input Voltage	24VDC
		Max Input Current	4.1A
		Connections	20AWG, Copper Conductors
	Mechanical	Circuit	Class 2
		Housing Construction	Flexible PCB Board, Silicone Jacket
	Environmental	Mounting Options	Channel
		Ingress Protection	IP20, IP65
		Certifications	cULus, CE, RoHS Compliant
		Operating Temperature	-4°F to 104°F (-20°C to 40°C)


Performance

CCT		3000K
Power	W/FT (W/m)	4.4 (14.4)
Lumens	lm/FT (lm/m)	470 (1,543)
Efficacy	lm/W	107
CRI	CRI	90+
Increment	inch (mm)	0.33 (8.33)
Max. Length	ft (m)	16ft 4in (5m)

Ordering

Product Code	CCT	IP Rating	Profile
BL flexFORM Premium Cut D3	3000K	IP20 IP65	

Dimensions



Section		A	B	C	D
		inch (mm)			
	DRY(IP20)	0.40 (10)	0.33 (8.33)	-	0.06 (1.5)
	DMP(IP65)	0.47 (12)	0.33 (8.33)	0.55 (14)	0.2 (4.5)

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information,
please download the
BL LIGHTING catalog

bllighting.com



Compatible Profile

- Compatibility chart is for DRY (IP20) tape only
- Measurements in inch (mm)

Dotting Table:

A = No visible dots

B = Slight visible dots

C = Clear visible dots



Surface Mount

	BL fixFORM SF Channel 2212		Dotting C	Spec Sheet
	BL fixFORM SF Square 2222		Dotting A	Spec Sheet
	BL fixFORM SF Rectangle 2232		Dotting A	Spec Sheet
	BL fixFORM SF Round 2221		Dotting A	Spec Sheet
	BL fixFORM SF Shallow 1709		Dotting B	Spec Sheet
	BL fixFORM SF Square 1617		Dotting A	Spec Sheet
	BL fixFORM SF Wide 4930 Requires 2 LED Strips		Dotting A	Spec Sheet
	BL fixFORM SF Focus Beam 30° Beam Spread Lens Optic		Dotting C	Spec Sheet
	BL fixFORM Recessed 3314 45° Angle Frosted Optic		Dotting B	Spec Sheet
	BL fixFORM SF Single Side 45 1616 45° Angle Frosted Optic		Dotting B	Spec Sheet
	BL fixFORM SF Double Side 45 Double Sided Frosted Lens Optic		Dotting B	Spec Sheet

Recessed Mount

	BL fixFORM Recessed 2626 In-Floor Profile		Dotting A	Spec Sheet
	BL fixFORM Recessed Shallow 2811 3/8" Recess Depth		Dotting C	Spec Sheet
	BL fixFORM Recessed 2416 Ceiling Flanged Extrusion		Dotting B	Spec Sheet
	BL fixFORM Recessed 4435 Ceiling Flanged Extrusion		Dotting A	Spec Sheet
	BL fixFORM Recessed Trimless 2414 Mud-In Drywall Channel		Dotting C	Spec Sheet

Specialty

	BL fixFORM SF Contour 1905 Bendable LED Channel		Dotting C	Spec Sheet
	BL fixFORM Stair Nose		Dotting B	Spec Sheet

Suspended

	BL fixFORM SP Round 2020 Suspended and Surface Mount Options Available		Dotting A	Spec Sheet
--	---	--	---------------------	----------------------------

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com

