

Delivering up to 128lm/FT and 90+ CRI, our dimmable BL flexFORM U Series LED tape flexes horizontally and vertically, and is perfect for intricate shapes in architectural backlighting, signage, channel letters, curved displays and coves of any shape or size. BL flexFORM Universal Bend adapts itself to any shape, the bendable ribbon takes corners and contours with ease, allowing much sharper horizontal turns than traditional LED Tape, and eliminating the need for jumper wires to take the bends. Add energy efficient accents to coves, under cabinets, bar shelving and displays in commercial, residential, and retail environments. BL flexFORM Universal Bend is compatible with BL fixFORM Profiles, and UL listed, custom lengths typically ship within 1-2 days!

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Up to 128 lm/FT

1.46W/FT

90+ CRI

Quick Ship

Product Detail



IP20

LOW

DIM

Bluetooth

CE

RoHS

cULus LISTED

5 YEAR WARRANTY

Lighting	Number of LED's	18/FT (60/m)
	Lamp	SMD 2835
	Beam Angle	120°
	Average Life	50,000 Hours
	CCT Binning	SDCM <3 LED's
Electrical	Controls	0-10V, MLV, ELV, Phase-Cut, Triac, DMX, Bluetooth
	Input Voltage	24VDC
	Max Input Current	4A
	Connections	20AWG, Copper Conductors
Mechanical	Circuit	Class 2
	Housing Construction	Flexible PCB Board
Environmental	Mounting Options	Clips, Adhesive
	Ingress Protection	IP20
	Certifications	cULus, CE, RoHS Compliant
Operating Temperature		-4°F to 104°F (-20°C to 40°C)

Performance


Ordering

CCT/Color		2700K	3000K	3500K	4000K	5000K	6500K
Power	W/FT (W/m)	1.46(4.8)					
Lumens	lm/FT (lm/m)	117 (385)	117 (385)	128 (420)	128 (420)	128 (420)	122 (400)
Efficacy	lm/W	80	80	88	88	88	84
CRI	CRI	90+					
Cut Marks	inch (mm)	3 - 15/16 (100)					
Max. Length	ft (m)	16ft 4in (5m)					

Product Code	CCT/Color	IP Rating
BL flexFORM U1		
	2700K	IP20
	3000K	
	3500K	
	4000K	
	5000K	
	6500K	

Dimensions

Bend Orientation



Section		A	B	C	D
		inch (mm)			
	DRY(IP20)	0.24 (6.0)	3.94 (100)	10ft(3m)	0.05 (1.2)

Vertical 90°

Horizontal 90°

BL flexFORM U Series can be bent freely in all directions, horizontally and vertically, to a maximum of 90° at the designated bending points.

## Compatible Profile

- Compatibility chart is for DRY (IP20) tape only
- Measurements in inch (mm)

### Dotting Table:

**A** = No visible dots

**B** = Slight visible dots

**C** = Clear visible dots



## Surface Mount

	BL fixFORM <b>SF Channel 2212</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Square 2222</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Rectangle 2232</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Round 2221</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Shallow 1709</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Square 1617</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Wide 4930</b> Requires 2 LED Strips		Dotting <b>A</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Focus Beam</b> 30° Beam Spread Lens Optic		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Recessed 3314</b> 45° Angle Frosted Optic		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Single Side 45 1616</b> 45° Angle Frosted Optic		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>SF Double Side 45</b> Double Sided Frosted Lens Optic		Dotting <b>C</b>	<a href="#">Spec Sheet</a>

## Recessed Mount

	BL fixFORM <b>Recessed 2626</b> In-Floor Profile		Dotting <b>B</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Recessed Shallow 2811</b> 3/8" Recess Depth		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Recessed 2416</b> Ceiling Flanged Extrusion		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Recessed 4435</b> Ceiling Flanged Extrusion		Dotting <b>B</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Recessed Trimless 2414</b> Mud-In Drywall Channel		Dotting <b>C</b>	<a href="#">Spec Sheet</a>

## Specialty

	BL fixFORM <b>SF Contour 1905</b> Bendable LED Channel		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
	BL fixFORM <b>Stair Nose</b>		Dotting <b>C</b>	<a href="#">Spec Sheet</a>

## Suspended

	BL fixFORM <b>SP Round 2020</b> Suspended and Surface Mount Options Available		Dotting <b>C</b>	<a href="#">Spec Sheet</a>
--	---	--	---------------------	----------------------------

## BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8  
P: 1-804-874-4405 E: info@bllighting.com  
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at [bllighting.com](http://bllighting.com) for current technical data.

For more information, please download the BL LIGHTING catalog

[bllighting.com](http://bllighting.com)

