# **BL grazeLINEAR GL30417**

Semi-Recessed Linear LED Wall Graze Luminaire 17W, 120V-277VAC



BL grazeLINEAR GL semi-recessed LED Linear Wall Washer is ideal for bathing walls with even illumination, providing wayfinding, accenting and grazing light over surfaces. Asymmetrical light distribution is emitted through the built in reflector, delivering precise, ultra low glare illumination where you need it. The attractive bezel is constructed of lightweight aluminum with white or black semi-recessed finish options, is suitable for dry and damp locations, and comes with spring clips or a mounting plate for easy installation into ceilings and walls with a modern, streamlined and minimalist style. Brighten corridors, add general lighting and frame your spaces with exceptionally smooth illumination. Graze light across contours and shadows and enhance halls, ballrooms, lobbies, offices, and public spaces by highlighting accent walls, signage, murals, decorative wall panels and other special features.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Up to 792lm/unit

120-277VAC

**Low Glare** 

**Asymmetrical Light Distribution** 

#### **Product Detail**














Lighting	Power	17W
	Average Life	36,000 Hours
Electrical	Controls	0-10V
	Voltage	43.4VDC (120-277VAC Power Supply Input)
	Current	350mA
	Circuit	Class 2
Mechanical -	Housing Construction	Extruded Aluminum (Black or White)
	Mounting	Optional Plaster Frame
Environmental	Ingress Protection	IP20
	Certifications	UL, FCC
	Operating Temperature	32°F to 95°F (0°C to 35°C)


#### **Performance**

Power	W/unit		17W	
ССТ	ССТ	2700K	3000К	4000K
Lumens	lm/unit	72	26	792
Efficacy	lm/W	4	.3	47
CRI	CRI	90+		

## Ordering



## **Dimensions**



### **Power Supply Detail**

Input	120 - 277 VAC	
Max. Output	out 275-1400mA   30/40/50W	
THD	< 20%	
Power Factor	> 0.9	
Dimming	0-10V	
Dimming Range	1-100%	
Startup Time	300ms	

Connections-Lead Type	Side Leads
Ingress Protection	IP20
Certifications	UL, FCC
Dimensions	Height - 21.8mm ( 0.86" ) Width - 26.0mm ( 1.02" ) Length - 98.5mm ( 3.88" )

#### **BL LIGHTING**

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com

For more information, BL LIGHTING catalog

bllighting.com

