BL inGROUND DISK FS48

Outdoor Recessed Wall Light 3W, 120-240VAC Input



BL inGROUND DISK FS48 recessed wall lights are built to blend seamlessly into the landscape, and ideal for stairway and pathway lighting. Available in 2000K, 3000K or 6000K CCT options. The unit is durably constructed with a die-cast aluminum body and front plate while the stainless steel mounting sleeve allows uniform and fast installations. Low profile and efficient, these luminaires are IP65 outdoor rated.

Up to 39 Im/unit 120-240VAC Input

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail





	Lighting	LED	SMD 3030
Lig		Power	3W
		Average Life	50,000 Hours
-	Electrical	Controls	Dali, PWM, Triac, 1-10V
El		Input Voltage	120-240VAC
		Operating Current (MA)	48
	Mechanical	Housing Construction	Dark Grey Powder Coated Aluminum
м		Front Cover	Dark Grey Powder Coated Aluminum
IVI		Mounting Sleeve	Stainless Steel
		Power Cable	3-Core 18AWG, Length = 1.6FT (0.5m)
	Environmental	Ingress Protection	IP65
E r		Certifications	ETL, CE, RoHS Compliant
EI		Impact Protection	IK10
		Operating Temperature	-4°F to 104°F (-20°C to 40°C)

Performance

Power	W/unit	3		
сст	ССТ	2000К	3000К	6000K
Lumens	Im/unit	33	36	39
Efficacy	lm/W	11	12	13
CRI	CRI	70	80	70

Ordering

Product Code	ССТ	Finish
BL inground DISK FS48		\vdash
	2000K	DG (Dark Grey -Standard)
	3000K	SG (Silver Grey)
	6000K	BK (Black)

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty. Designed & Assembled in North America.


For more information, please downlad the BL LIGHTING catalog






Dimensions


DISK FS48








Recessed Mounting Sleeve




Photometric Details

Illuminance

1 m	
32ft (10m)	0.02 LUX
26ft (8m)	0.04 LUX
20ft (6m)	0.06 LUX
13ft (4m)	0.14 LUX
6.5ft (2m)	0.56 LUX
3 2 1 BL inGROUND DI	о 1 2 3 SK FS48 (3000K)



Light Distribution



BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty. Designed & Assembled in North America.

For more information please downlad the BL LIGHTING catalog



2