

When true incandescent is a must-have, the fully customizable BL spotGLOBE INC Series string light is a highly flexible solution. Traditional, classic, and romantic. Incandescent lamps are suitable for higher ambient temperatures. Designed to meet a variety of potential applications and environments, such as restaurants, sun decks and alleyways. Festoon lights across landscapes, patio, and walkways; accent building outlines and add impact to signs.

-4°F to 104°F (-20°C to 40°C)

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

## Product Detail



<b>Lighting</b>	Lamp	Incandescent, Clear Optic
	Power	5W
	Average Life	10,000 Hours
	Lumens	28 lm/Lamp
	Efficacy	5.6 lm/W
<b>Electrical</b>	Controls	MLV Dimming
	Input Voltage	24VAC
	Max Input Current	5A, Maximum 18 Lamps per Series
	Connections	16AWG, Copper Conductors
<b>Mechanical</b>	Circuit	Class 2
	Housing Construction	UV Stabilized Polycarbonate Globe
	Base	E10
	Weight	0.049lb (22g)/ea
<b>Environmental</b>	Operating Temperature	-4°F to 104°F (-20°C to 40°C)
	Ingress Protection	IP65
	Mounting	Insulated Clip, Aircraft Cable
	Lamp Spacing	3", 4", 6", 9", 12", 18", 24"
	Certifications	cULus, CE



## Ordering

Product Code	Lamp Spacing
BL SpotGLOBE INC	
	03 = 3" o.c.
	04 = 4" o.c.
	06 = 6" o.c.
	09 = 9" o.c.
	12 = 12" o.c.
	18 = 18" o.c.
	24 = 24" o.c.

## Max. Length

3" o.c.	4.5ft
4" o.c.	6ft
6" o.c.	9ft
9" o.c.	13ft
12" o.c.	18ft
18" o.c.	27ft
24" o.c.	36ft

## Dimensions

