

The BL controls Cato is a wall-mounted DMX controller designed for the most demanding projects, featuring 1024 channels, 2 universes, 500 scenes and 10 zones. The glass panel interface features an intuitive and user-friendly, touch-sensitive color display, allowing simple selection of up to 50 scenes, along with speed, dimming, saturation and RGBW color control. Connect to a computer or smart device to create your own programs or for remote control.

Touchscreen Panel Programmable on Windows/Mac Smart Phone App

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Electrical	Input Voltage	6VDC, 0.6A (Plug-in power supply included)
	Connections	1 Mini-USB 2.0 RS232 Ethernet 8 Dry Contact Points 5V Output Relay
Mechanical	Housing Construction	Glass Touch Panel Black Frame
	Mounting	Single or Double Gang Wall Socket
	Weight	0.54lb (247g)
Environmental	Environmental	IP20
	Certifications	ETL
	Operating Temperature	14°F to 113°F (-10°C to 45°C)

Features

- DMX 512 Protocol
- 2 Universes
- Intuitive Control Palette
- LCD Screen
- Clock & Calendar Trigger
- Mac OSX and Windows
- Smart Phone App

Ordering

Product Code	Series	Channels	Input Voltage	IP Rating
CTO	CT	1024	6	IP20

Dimensions

