

BL Controls Decoder SPI converts DMX signal to Serial Peripheral Interface (SPI), enabling high speed data transmission and strong signal integrity. Easy to configure via an OLED panel, works with common pixel protocols.


|              |  |
|--------------|--|
| CLIENT       |  |
| PROJECT NAME |  |
| LOCATION     |  |
| DATE         |  |

**Quick Ship**

## Product Detail



|                      |                       |                               |
|----------------------|-----------------------|-------------------------------|
| <b>Electrical</b>    | Input Voltage         | 5 - 24VDC                     |
|                      | Max Input             | 0.2A                          |
|                      | Input Signal          | DMX                           |
|                      | Output Signal         | SPI                           |
|                      | DMX Channels          | 512                           |
| <b>Mechanical</b>    | Connection Type       | Spring wire connector         |
|                      | Housing Construction  | Plastic, White                |
|                      | Weight                | 0.28lb (126g)                 |
|                      | Panel                 | OLED                          |
| <b>Environmental</b> | Environmental         | IP20                          |
|                      | Certifications        | UR, CE, RoHS                  |
|                      | Operating Temperature | -4°F to 122°F (-20°C to 50°C) |



**RoHS**

## Ordering

| Product Code | Series | Input Voltage | IP Rating |
|--------------|--------|---------------|-----------|
| DCSPI        | CT     | 24            | IP20      |

## Dimensions

