

Continuous run lengths up to 150FT are achievable on a single plug, with our flexible, 120V LED ribbon. Perfect for architectural accents and certified for indoor and outdoor use, easily add highlights to soffits, coves, under cabinets, bar shelving and displays, in commercial, residential, and retail environments. L1 produces a uniform 146 lm/FT, is simple to install with mounting clips or channel, and UL listed, custom lengths ship within 1-2 days!

Up to 130 lm/ft

150ft on a single plug

Quick Ship

<b>CLIENT</b>	
<b>PROJECT NAME</b>	
<b>LOCATION</b>	
<b>DATE</b>	

**Product Detail**



<b>Lighting</b>	Number of LED's	18 Diodes/FT (60/m)
	Lamp	SMD 5050
	Beam Angle	120°
	Average Life	30,000 Hours
<b>Electrical</b>	CCT Binning	SDCM <3 LED's
	Input Voltage	120VAC
	Connections	Male Socket Plugin
<b>Mechanical</b>	Housing Construction	Flexible PCB Board, PVC Jacket
	Mounting Options	Clips, PVC Channel, Adhesive
<b>Environmental</b>	Ingress Protection	IP65
	Certifications	ETL
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)


**Performance**

CCT/Color		3000K	4000K
<b>Power</b>	W/FT (W/m)	2.5 (8.2)	
<b>Lumens</b>	lm/FT (lm/m)	120 (394)	130 (427)
<b>Efficacy</b>	lm/W	48	52
<b>CRI</b>	CRI	90	
<b>Increment</b>	inch (mm)	17.72 (450)	
<b>Max. Length</b>	ft (m)	150ft (45.7m)	

**Ordering**

Product Code	Series	CCT	Input Voltage	IP Rating
L1	F		120	IP65
		3000K		
		4000K		

**Dimensions**



Section	DMP(IP65)	A	B	C	D
		inch (mm)			
		0.56 (14.5)	17.72 (450)	5ft(1.5m)	0.31 (8)

