

LG9 RGBW

BL Inground Grazer

LED Inground Grazer, Outdoor,
Up to 36W, 100-277VAC



LIGHTING
SINCE 1986

LG9 RGBW is a dynamic inground wall grazer designed for architectural and landscape lighting. Its aluminum housing and 316 stainless steel trim support static loads up to 330lb (150kg), delivering up to 1660lm/unit. Featuring RGBW color mixing with DMX/RDM control and an adjustable 12° tilt for flexible beam control, it enables precise, vibrant illumination. With multiple beam angles, IP67/IK08 protection, and durable construction, the **LG9 RGBW** delivers reliable performance in outdoor environments.

Up to 1660 lm/unit | 100-277VAC | 1.64FT and 3.28FT Length Options

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	No. of LEDs/unit	12 (1.64FT/500mm), 24 (3.28FT/1000mm)
	Lamp	TX Series
	Beam Angle	20°, 30°, 45°, 20° x 50°
	CCT Binning	3 Step
	Power	18W (1.64FT/500mm), 36W (1.64FT/500mm)
Electrical	Average Life	50,000 Hours
	Controls	DMX, RDM
	Max Input Current	0.36A
	Input Voltage	100-277VAC
	Input Frequency	50-60Hz
Mechanical	Connections	3 x 16AWG + 3 x 22AWG
	Housing Construction	Aluminum Body, 316 Stainless Steel Cover Frame
	Mounting	Inground
	Weight	19.69" (500mm): 8.53 lb (3.87kg) 39.37" (1000mm): 16.7 lb (7.58kg)
	Dimensions (mm)	L:19.69" x D: 3.54" x H:4.37" (L:500 x D:90 x H:111) L:39.37" x D:3.54" x H:4.37" (L:1000 x D:90 x H:111)
Environmental	Max Static Load	330lb (150kg)
	Ingress Protection	IP67
	Impact Protection Rating	IK08
	Certifications	ETL, CE, RoHS
	Operating Temperature	-4°F to 122°F (-20°C to 50°C)

Ordering

Product Code	Series	Length	CCT	Beam Angle	Diffuse	Controls	Finish	Input Voltage	IP Rating
LG9C	GW	1.64FT	RGBW (2700K)	20°	CL = Clear Lens	DMX	BK = Black	UNI	IP67
		3.28FT	RGBW (3000K)	30°	GL = Anti-Glare Lens	RDM			
			RGBW (4000K)	45°					
			RGBW (6500K)	20°x50°					

BL LIGHTING

ILLUMINATE EVERYTHING

III - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 E: info@blighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at blighting.com for current technical data.

For more information,
please download the
BL LIGHTING catalog

blighting.com



Performance**Clear Lens : 1.64FT (500mm)**

CCT/Color		RGBW (2700K)	RGBW (3000K)	RGBW (4000K)	RGBW (6500K)
Power	W/Unit			18	
Lumens	lm/Unit			830	
Efficacy	lm/W			46	
CRI	CRI			80+	

Clear Lens : 3.28FT (1000mm)

RGBW (2700K)	RGBW (3000K)	RGBW (4000K)	RGBW (6500K)
		36	
		1660	
		46	
		80+	

Anti-Glare Lens : 1.64FT (500mm)

CCT/Color		RGBW (2700K)	RGBW (3000K)	RGBW (4000K)	RGBW (6500K)
Power	W/Unit			18	
Lumens	lm/Unit			497	
Efficacy	lm/W			28	
CRI	CRI			80+	

Anti-Glare Lens : 3.28FT (1000mm)

RGBW (2700K)	RGBW (3000K)	RGBW (4000K)	RGBW (6500K)
		36	
		944	
		28	
		80+	

Dimensions