

LG9

BL Inground Grazer

LED Inground Grazer, Outdoor,
Up to 36W, 100-277VAC



BL LIGHTING
SINCE 1986

LG9 is a high-performance inground wall grazer designed for architectural and landscape lighting. Its aluminum housing and 316 stainless steel trim support static loads up to 330lb (150kg), delivering up to 3406lm/unit. Featuring multiple beam angles with an adjustable 12° tilt for flexible beam control and static white options from 2700K to 6500K, it provides precise, glare-free illumination. Rated IP67/IK08 and compatible with 0-10V, TRIAC, and ELV controls, the **LG9** ensures reliable outdoor performance.

Up to 3406 lm/unit

100-277VAC

1.64FT and 3.28FT Length Options

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



IP67



0-10V



ELV



IK08 PROTECTION



5 YEAR WARRANTY



ETL



CE



RoHS

Lighting	No. of LEDs/unit	12 (1.64FT/500mm), 24 (3.28FT/1000mm)
	Lamp	SMD 3535 LED
	Beam Angle	Clear Lens: 13°, 35°, 55°, 15° x 40° Anti-Glare Grid: 13°, 25° x 35°, 35° x 50°, 15° x 40°
	CCT Binning	3 Step
	Power	18W (1.64FT/500mm), 36W (3.28FT/1000mm)
	Average Life	50,000 Hours
Electrical	Controls	0-10V, TRIAC, ELV
	Max Input Current	0.36A
	Input Voltage	100-277VAC
	Input Frequency	50-60Hz
Mechanical	Connections	3 x 16AWG (TRIAC), 3 x 16AWG + 3 x 22AWG (Others)
	Housing Construction	Aluminum Body, 316 Stainless Steel Cover Frame
	Mounting	Inground
	Weight	19.69" (500mm): 8.27 lb (3.75kg) 39.69" (1000mm): 16.31 lb (7.4kg)
	Dimensions	L:19.69" x D:3.54" x H:4.37" (L:500 x D:90 x H:111) L:39.37" x D:3.54" x H:4.37" (L:1000 x D:90 x H:111)
	Max Static Load	330lb (150kg)
Environmental	Ingress Protection	IP67
	Impact Protection Rating	IK08
	Certifications	ETL, CE, RoHS
	Operating Temperature	-4°F to 122°F (-20°C to 50°C)

Ordering

Product Code	Series	Length	CCT	Beam Angle		Diffuse	Controls	Finish	Input Voltage	IP Rating
LG9	GW								UNI	IP67
		1.64FT	2700K	Clear Lens	Anti-Glare Lens	CL = Clear	NO	BK = Black		
		3.28FT	3000K	13°	13°	GL = Anti-Glare Lens	010V			
			3500K	35°	25°x35°		TRIAC			
			4000K	55°	35°x50°		ELV			
			5000K	15°x40°	15°x40°					
			6500K							

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@blighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at blighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

blighting.com



Performance

Clear Lens : 1.64FT (500mm)

CCT/Color		2700K	3000K	3500K	4000K	5000K	6500K
Power	W/unit	18					
Lumens	lm/unit	1703					
Efficacy	lm/W	94					
CRI	CRI	80+					

Clear Lens : 3.28FT (1000mm)

2700K	3000K	3500K	4000K	5000K	6500K
36					
3406					
94					
80+					

Anti-Glare Lens : 1.64FT (500mm)

CCT/Color		2700K	3000K	3500K	4000K	5000K	6500K
Power	W/unit	18					
Lumens	lm/unit	1088					
Efficacy	lm/W	60					
CRI	CRI	80+					

Anti-Glare Lens : 3.28FT (1000mm)

2700K	3000K	3500K	4000K	5000K	6500K
36					
2176					
60					
80+					

Dimensions

