

LN1171

BL Arealinear

Linear LED Wall Washer
Up to 90W, 100-277VAC



Powerful, efficient, and engineered to deliver exceptional wall washing, grazing and architectural highlighting of exterior facades, signage, bridges and monuments. With an impressive output of up to 12150 lumens, in seven beam angle options. Durably constructed with anodized aluminum housing, shatter-resistant glass lens, weatherproof line voltage power cables, integral 100-277VAC power supply, DMX decoder, and two, 160° on board adjustable mounting brackets that allow for precise light distribution. Perfect for dynamic illumination of spatial envelopes in urban settings.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Up to 12150lm/unit

100-277VAC

Product Detail



Lighting	Power	30W (1.77FT), 60W (3.39FT), 90W(5FT)
	Average Life	50,000 Hours
Electrical	Controls	DMX, Bluetooth
	Input Voltage	100-277VAC
	Power Cord Length	2ft (0.6m), extendable
	DMX Cords Length	2ft (0.6m), extendable
Mechanical	Housing Construction	Aluminum Body, Tempered Glass Lens
	Weight	1.77FT: 3.2kg (7.05lb)
		3.39FT: 4.5kg (9.92lb)
		5FT: 5.7kg (12.57lb)
	Dimensions (mm)	L:21.26" x D:2.80" x H:4.53" (L:540 x D:71 x H:115) L:40.75" x D:2.80" x H:4.53" (L:1035 x D:71 x H:115) L:60.24" x D:2.80" x H:4.53" (L:1530 x D:71 x H:115)
Mounting	Integrated 160° Adjustable Mounting Bracket	
Accessories	PCH LN1171	Power Cable 3-pin Connector (5FT, 15FT, 30FT)
	PCE LN1171	Power Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PH LN1171	DMX Cable 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PE LN1171	DMX Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	M3P LN1171	End Cap (3-Pin Cable)
Environmental	Ingress Protection	IP67
	Certifications	cLCus
	Operating Temperature	-40°F to 113°F (-40°C to 45°C)



Ordering

Product Code	Series	Length	CCT	Beam Angle	Finish	Input Voltage	IP Rating
LN1171	L					UNI	IP67
		1.7FT	2700K	8°	DG = Dark Gray		
		3.4FT	3000K	15°	BK = Black		
		5FT	4000K	25°	WH = White		
			6500K	40°			
			60°				
			10°x30°				
				10°x50°			

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com



Performance

Fixture Length: 1.77FT (540mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	30			
Lumens	lm/unit	4050			
Efficacy	lm/W	135			

Fixture Length: 3.39FT (1035mm)

CC T/Color		2700K	3000K	4000K	6500K
Power	W/unit	60			
Lumens	lm/unit	8100			
Efficacy	lm/W	135			

Fixture Length: 5FT (1530mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	90			
Lumens	lm/unit	12150			
Efficacy	lm/W	135			

Dimensions

