

Powerful, efficient, and engineered to deliver exceptional wall washing, grazing and architectural highlighting of exterior facades, signage, bridges and monuments. With an impressive output of up to 12150 lumens, in eight beam angle options. Durably constructed with anodized aluminum housing, shatter-resistant glass lens, weatherproof line voltage power cables, integral 100-277VAC power supply, DMX decoder, and two, 160° on board adjustable mounting brackets that allow for precise light distribution. Perfect for dynamic illumination of spatial envelopes in urban settings.

Up to 12150lm/unit

100-277VAC

## Product Detail



<b>Lighting</b>	Power	30W (1.77FT), 60W (3.39FT), 90W(5FT)
	Average Life	50,000 Hours
	Controls	DMX, Bluetooth
<b>Electrical</b>	Input Voltage	100-277VAC
	Power Cord Length	2ft (0.6m), extendable
	DMX Cords Length	2ft (0.6m), extendable
	Housing Construction	Aluminum Body, Tempered Glass Lens
		1.77FT: 3.2kg (7.05lb)
<b>Mechanical</b>	Weight	3.39FT: 4.5kg (9.92lb)
		5FT: 5.7kg (12.57lb)
	Dimensions (mm)	L:21.26" x D:2.80" x H:4.53" (L:540 x D:71 x H:115) L:40.75" x D:2.80" x H:4.53" (L:1035 x D:71 x H:115) L:60.24" x D:2.80" x H:4.53" (L:1530 x D:71 x H:115)
	Mounting	Integrated 160° Adjustable Mounting Bracket
<b>Accessories</b>	PCH LN1171	Power Cable 3-pin Connector (5FT, 15FT, 30FT)
	PCE LN1171	Power Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PH LN1171	DMX Cable 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PE LN1171	DMX Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	M3P LN1171	End Cap (3-Pin Cable)
<b>Environmental</b>	Ingress Protection	IP67
	Certifications	cLCus
	Operating Temperature	-40°F to 113°F (-40°C to 45°C)

## Ordering

Product Code	Series	Length	CCT	Beam Angle	Finish	Input Voltage	IP Rating
LN1171	L	1.7FT	2700K	4°	DG = Dark Gray	UNI	IP67
		3.4FT	3000K	8°	BK = Black		
		5FT	4000K	10°x50°	WH = White		
			6500K	15°			
				15°x30°			
				25°			
				40°			
				60°			



## Performance

### Fixture Length: 1.77FT (540mm)

CCT/Color		2700K	3000K	4000K	6500K
<b>Power</b>	W/unit		30		
<b>Lumens</b>	lm/unit		4050		
<b>Efficacy</b>	lm/W		135		

### Fixture Length: 3.39FT (1035mm)

CC T/Color		2700K	3000K	4000K	6500K
<b>Power</b>	W/unit		60		
<b>Lumens</b>	lm/unit		8100		
<b>Efficacy</b>	lm/W		135		

### Fixture Length: 5FT (1530mm)

CCT/Color		2700K	3000K	4000K	6500K
<b>Power</b>	W/unit		90		
<b>Lumens</b>	lm/unit		12150		
<b>Efficacy</b>	lm/W		135		

## Dimensions

