

Powerful, efficient, and engineered to deliver exceptional wall washing, grazing and architectural highlighting of exterior facades, signage, bridges and monuments. With an impressive output of up to 8100 lumens, in eight beam angle options. Durably constructed with anodized aluminum housing, shatter-resistant glass lens, weatherproof line voltage power cables, integral 100-277VAC power supply, DMX decoder, and two, 160° on board adjustable mounting brackets that allow for precise light distribution. Perfect for dynamic illumination of spatial envelopes in urban settings.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Up to 8100lm/unit

100-277VAC

Product Detail



Lighting	Power	30W (1.77FT), 60W (3.39FT)
	Average Life	50,000 Hours
Electrical	Controls	DMX, Bluetooth
	Input Voltage	100-277VAC
	Power Cord Length	2ft (0.6m), extendable
	DMX Cords Length	2ft (0.6m), extendable
	Housing Construction	Aluminum Body, Tempered Glass Lens
Mechanical	Weight	1.77FT: 3.2kg (7.05lbs) 3.39FT: 4.5kg (9.92lbs)
	Dimensions (mm)	L:21.26" x D:2.80" x H:4.53" (L:540 x D:71 x H:115) L:40.75" x D:2.80" x H:4.53" (L:1035 x D:71 x H:115)
	Mounting	Integrated 160° Adjustable Mounting Bracket
Accessories	PCH LN1171	Power Cable 3-pin Connector (5FT, 15FT, 30FT)
	PCE LN1171	Power Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PH LN1171	DMX Cable 3-pin Connector (5FT, 15FT, 30FT)
	DMX 3PE LN1171	DMX Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	M3P LN1171	End Cap (3-Pin Cable)
Environmental	Ingress Protection	IP67
	Certifications	ETL
	Operating Temperature	-40°F to 122°F (-40°C to 50°C)

Performance

Fixture Length: 1.77FT (540mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	30			
Lumens	lm/unit	4050			
Efficacy	lm/W	135			

Fixture Length: 3.39FT (1035mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	60			
Lumens	lm/unit	8100			
Efficacy	lm/W	135			

Ordering

Product Code	Series	Length	CCT	Beam Angle	Finish	Input Voltage	IP Rating
LN1171	L	1.7FT	2700K	4°	DG = Dark Gray	UNI	IP67
		3.4FT	3000K	8°	BK = Black		
			4000K	10°x50°	WH = White		
			6500K	15°			
				15°x30°			
				25°			
				40°			
				60°			

