

LN1616

BL Arealinear

Linear LED Wall Washer
Up to 168W, 100-277VAC



Powerful, efficient, and engineered to deliver exceptional wall washing, grazing and architectural highlighting of exterior facades, signage, bridges and monuments. Vertically illuminate buildings with light projection with an impressive output of up to 20000 lumens, in seven beam angle options. Durably constructed with aluminum housing, shatter-resistant glass lens, weatherproof line voltage power cables, integral 100-277VAC power supply, and a 45° on board adjustable mounting bracket. Perfect for dynamic illumination of spatial envelopes in urban settings.

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Up to 20000lm/unit 100-277VAC 2FT, 3FT, 4FT and 5FT Length Options

Product Detail



Lighting	Power	67W (2FT), 100W (3FT), 135W (4FT), 168W (5FT)
	Average Life	50,000 Hours
Electrical	Controls	DMX, Bluetooth
	Input Voltage	100-277VAC
Mechanical	Housing Construction	Aluminum Body, Tempered Glass Lens
	Weight	4.2kg/9.26lbs (2FT), 6.0kg/13.23lbs (3FT), 8.2kg/18.07lbs (4FT), 9.9kg/21.83lbs (5FT)
	Dimensions	L:24.88" x D:6.42" x H:6.30" (L:632 x D:163 x H:160) L:36.42" x D:6.42" x H:6.30" (L:925 x D:163 x H:160) L:48.11" x D:6.42" x H:6.30" (L:1222 x D:163 x H:160) L:59.72" x D:6.42" x H:6.30" (L:1517 x D:163 x H:160)
	Mounting	Integrated 45° Adjustable Mounting Bracket
	PCH LN1616	Power Cable 3-pin Connector (5FT, 15FT, 30FT)
Accessories	PCE LN1616	Power Cable Extension 3-pin Connector (5FT, 15FT, 30FT)
	DMX 4PH LN1616	DMX Cable 4-pin Connector (5FT, 15FT, 30FT)
	DMX 4PE LN1616	DMX Cable Extension 4-pin Connector (5FT, 15FT, 30FT)
	M4P LN1616	End Cap (4-Pin Cable)
Environmental	Ingress Protection	IP67
	Certifications	ETL
	Operating Temperature	-40°F to 113°F (-40°C to 45°C)

Ordering

Product Code	Series	Length	CCT	Beam Angle	Finish	Input Voltage	IP Rating
LN1616	L					UNI	IP67
		2FT	2700K	8°	GR = Gray		
		3FT	3000K	10°x50°	BK = Black		
		4FT	4000K	15°	WH = White		
		5FT	6500K	15°x30°			
				25°			
				40°			
				60°			

BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com



Performance

Fixture Length: 2.07FT (632mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	67			
Lumens	lm/unit	8000			
Efficacy	lm/W	120			

Fixture Length: 3.04FT (925mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	100			
Lumens	lm/unit	12000			
Efficacy	lm/W	120			

Fixture Length: 4.01FT (1222mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	135			
Lumens	lm/unit	16000			
Efficacy	lm/W	119			

Fixture Length: 4.98FT (1517mm)

CCT/Color		2700K	3000K	4000K	6500K
Power	W/unit	168			
Lumens	lm/unit	20000			
Efficacy	lm/W	119			

