Mira

BL Fibersource



Mira is an efficient 18W LED illuminator, emitting a bright 3000K or 4000K white light output of 1820 lm. With a low profile and compact body measuring just 8.75"x4.5"x3.2" Mira fits easily into small and narrow spaces, and can be dimmed manually or with 010V or DMX protocols. Perfect for small projects, niche accents, and BL Fiberoptic Starfields.

Up to 1820lm Output

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail











Lighting	CCT	3000K, 4000K	
	Average Life	36,000 Hours	
Electrical	Controls	DMX, 0-10V (Source only), Switch	
	Input Voltage	90V-264VAC	
	PSU Output	24VDC	
	Temp. Range	14°F to 113°F (-10°C to 45°C)	
Mechanical	Housing Construction	ABS	
	Environmental	IP20	
	Aperture Diameter	1-3/16" (30mm)	
	Weight	2.03b (920g)	

Performance


CCT/Color		3000К	4000K	
Power	W/unit	18W		
Lumens	lm/unit	1770	1820	
Efficacy	lm/W	98	101	
CRI		80		

Ordering

Product Code Se	ries	Color	Effect	Controls	IP Rating
MRA F	0		+ -		IP20
		3000K	TW (Twinkle Wheel)	NO (No Dimming)	
		4000K		010V	
				DMX	

Dimensions





BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information BL LIGHTING catalog

bllighting.com

