

The BL controls Nero conveniently integrates DMX and Bluetooth 5.0 Mesh signals and is ideal for multi-zone and multi-scene lighting control. With up to 16 scenes, 4 zones and 16 pre-set programs, easily configure your lighting via mobile app or the intelligent touchscreen panel. The attractive wall mount controller is durably constructed with an aircraft aluminum housing and 2.5D tempered glass panel and intuitive touchscreen interface is easy to use with color wheel, push button selection and responsive haptic feedback. Installation is simplified with wireless transmission of DMX signals over long distances using Bluetooth 5.0 Mesh with up to 165ft (50m) range.

165ft (50m) Range Bluetooth

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail

Bluetooth DMX512

		1 2-2	R		Electrical	Input Voltage	12-24VDC
	- 11		4		Electrical	Power	2.4W
	_	-			Mechanical	Housing Construction	Aluminum Frame, 2.5D Tempered Glass
	_		1		Mechanical	Weight	225g
		(O				Wireless Protocol	Bluetooth 5.0 SIG Mesh
		\sim				Output Signal	DMX
					Controls	Zones	4
			В		Controis	Scenes	4 Per Zone
				_		DMX Channels	512
00	A	O MX	*	c(UL)us		Control	Touchpanel, Wireless (Via App)
IP20	LOW	DMX	Bluetooth	LISTED		Ingress Protection	IP20
cc	Dallo	Гœ			Environmental	Certifications	UL, CE, RoHS, FCC
CE	RoHS	FC				Operating Temperature	-4°F to 131°F(-20°C to 55°C)

16 pre-set Programs

Features

Bluetooth 5.0 SIG Mesh	Touch Sensitive Wheel & Buttons With Haptic Feedback		
• 165ft (50m) Range Bluetooth	• 2.5D Tempered Glass Panel, Touchscreen Interface		
• DMX 512	Durable Aircraft Aluminum Housing		
• 16 pre-set Programs	Remote Control With Smart Device Via App		
• 4 Zones, Up to 16 Scenes Per Zone	Attractive Wall Mount Controller		

Auto Program Modes

P1 - 3 Color Jump	P5 - Red/Green Fade	P9 - Blue/Purple Fade	P13 -Blue/White Fade
P2 - 7 Color Jump	P6 - Red/Blue Fade	P10 - Green/Yellow Fade	P14 - Yellow/Cyan Fade
P3 - White Strobe	P7 - Green/Blue Fade	P11 - Blue/Cyan Fade	P15 - 3 Color Fade
P4 - 7 Color Strobe	P8 - Red/Yellow Fade	P12 - Red/Purple Fade	P16 - Full Color Fade

Ordering Dimensions BACK VIEW SIDE VIEW TOP VIEW Product Code 43.5 BL-controls-NT4-DMX-512-BT-24V-IP20 **⊂**0 0 [1.71″] 120 120 84 20 00 [4.72"] [3.30″] [4.72"] [0.79"] 00000 75 29.5 [1.16″] [2.95"] For more information **BL LIGHTING** se download the ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against prema-ture failure. Lack of surge protection may void your warranty. Designed & Assembled in North America.

BL LIGHTING catalog bllighting.com