

O4 100W

BL Power

Standard LED Driver
100W, Constant Voltage, 24VDC




O4 is a Class 2, constant voltage, 24VDC LED Driver and is perfectly compatible with low-voltage, DMX or Bluetooth systems. Features include 110-277VAC input voltage and side mount tabs for ease of installation, with compact designs that are easy to fit into compatible BL Cbox and standard electrical junction boxes and enclosures.

Quick Ship

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Electrical

Input Voltage	110-277VAC
Input Frequency	50-60 Hz
Input Current	1.1A@110V, 0.44A@277V
Output Voltage	24VDC, Constant Voltage
Power	100W
Min. Power Draw	10W
Dimming	N/A
Max. Output Current	4.1A
Connections	18 AWG, Copper Conductors
Start-up Time	<1000ms
Ambient Temperature	-40°F to 122°F (-40°C to 50°C)
Max. Case Temperature	178°F (81°C)
Circuit	Class 2
Average Life	50,000 hours


Mechanical

Housing Construction	Anodized Aluminum
Weight	1.1lb (500g)
Environmental	IP64

Ordering

Product Code	Series	Power	Output	Input Voltage	IP Rating
O4ST	P	100W	24	UNI	IP64

Dimensions



BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com

