

P10 is a compact fiber optic end fixture designed for seamless integration into architectural and landscape settings. Constructed with durable 316 stainless steel and a clear or frosted 1.38" tempered glass lens, it provides side light transmission for steps, pathways, and accent lighting. The clear lens offers stronger projection, while the frosted lens creates a soft marker effect. Designed for recessed mounting, it supports fiber sizes from 0.08" to 0.31" and withstands up to 1,125 lbs of pressure. Rated IP65 and operable from 14°F to 113°F, P10 delivers reliable performance in both indoor and outdoor environments.

14°F to 113°F (-10°C to 45°C)

Walkover

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



IP65

Lighting	Beam Angle	65°
	Housing Construction	316 Stainless Steel, Tempered Glass
	Optics	Ø1.38" (Ø35mm) Flat Clear or Frosted Lens
Mechanical	Weight Bearing	1125lb (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.4lb (180g)
	Ingress Protection	IP65
Environmental	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)

Ordering

Product Code	Series	Optics
P10	PV	
		CL = Clear
		FR = Frosted

Dimensions

