P12

BL Fiberoptic



P12 is a durable, walkover-rated fiber optic end fixture designed for clean, low-profile lighting in architectural and landscape environments. Built from 316 stainless steel with a flat clear or frosted 0.79" tempered glass lens, P12 delivers a focused 45° beam ideal for accenting paths, steps, or facade features. Recessed for seamless installation, it handles fiber sizes from 0.08" to 0.31" and supports up to 1,125 lbs of pressure. Weighing 0.2 lbs and rated IP65, P12 performs reliably in outdoor and indoor settings across a wide temperature range of 14°F to 113°F.

CLIENT PROJECT NAME LOCATION DATE

14°F to 113°F (-10°C to 45°C)

Walkover


Product Detail




Lighting	Beam Angle	45°
Mechanical	Housing Construction	316 Stainless Steel, Tempered Glass
	Optics	Ø0.79" (Ø20mm) Flat Clear or Frosted Lens
	Weight Bearing	1125lb (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.2lb (92g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)



Ordering



Dimensions



BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.





