

P13 is an ultra-compact, fiber optic end fixture ideal for precision lighting in architectural and landscape settings. Crafted from 316 stainless steel with a flat clear or frosted 0.39" tempered glass lens, it emits a wide 70° beam for gentle light diffusion. Designed for recessed installation, it accommodates fiber sizes from 0.08" to 0.31" and bears loads up to 1,125 lbs. Weighing 0.02 lbs, P13 is perfect for discreet applications requiring a minimal footprint. Rated IP65 and operable from 14°F to 113°F, it offers durable performance indoors or out.

14°F to 113°F (-10°C to 45°C)

Walkover

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	Beam Angle	70°
	Housing Construction	316 Stainless Steel, Tempered Glass
	Optics	Ø0.39" (Ø10mm) Flat Clear or Frosted Lens
Mechanical	Weight Bearing	1125lb (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.02lb (10.5g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)



Ordering

Product Code	Series	Optics
P13	PV	
		CL = Clear
		FR = Frosted

Dimensions

