P18

BL Fiberoptic



P18 is a compact, recessed fiber optic end fixture designed for subtle yet effective accent lighting. Built from 316 stainless steel with a domed clear or frosted 0.51" tempered glass lens, it provides a beam angle between 20° and 40°, depending on fiber depth. Ideal for architectural and landscape installations, it supports fiber sizes from 0.08" to 0.31" and weighs just 0.03 lbs. Rated IP65 and operable from 14°F to 113°F, it offers durable performance indoors or out.

14°F to 113°F (-10°C to 45°C)

CLIENT	
PROJECT NAME	
LOCATION	
DATE	


Product Detail




Lighting	Beam Angle	20° - 40° (Beam angle determined by fiber depth)
	Housing Construction	316 Stainless Steel, Tempered Glass
Mechanical	Optics	Ø0.51" (Ø13mm) Domed Clear or Frosted Lens
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.03lb (13.3g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)



Ordering



Dimensions



BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.





