P20

BL Fiberoptic



P20 is a walkover-rated fiber optic end fixture built for durability in demanding architectural and landscape settings. Featuring a 316 stainless steel body and a flat clear or frosted 1.5" tempered glass lens, it delivers a wide 75° beam for broad light distribution. Designed for recessed mounting, **P20** supports fiber sizes from 0.08" to 0.31" and handles loads up to 1,125 lbs. Weighing 1.1 lbs and rated IP65, it ensures reliable, weather-resistant performance from 14°F to 113°F.

PROJECT NAME
LOCATION
DATE

14°F to 113°F (-10°C to 45°C)

Walkover


Product Detail




Lighting	Beam Angle	75°
Mechanical	Housing Construction	316 Stainless Steel, Tempered Glass
	Optics	Ø1.5" (Ø38mm) Flat Clear or Frosted Lens
	Weight Bearing	1125lb (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	1.1lb (497.1g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)



Ordering



Dimensions



BL LIGHTING

ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC. Canada. V6P 3S8 P: 1-604-874-4405 E: info@bllighting.com Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved. Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog



