

P22 is a rugged, recessed fiber optic end fixture designed for seamless integration in architectural and landscape environments. Crafted from 316 stainless steel with a flat clear or frosted square 0.69" tempered glass lens, it delivers a focused 45° beam for precise lighting. Rated for walkover use, it supports fiber sizes from 0.08" to 0.31" and withstands up to 1,125 lbs. At just 0.18 lbs, P22 is lightweight yet durable. Rated IP65 and operable from 14°F to 113°F, it offers durable performance indoors or out.

14°F to 113°F (-10°C to 45°C)

Walkover

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	Beam Angle	45°
	Housing Construction	316 Stainless Steel, Tempered Glass
Mechanical	Optics	□0.69" (□17.5mm) Flat Clear or Frosted Square Lens
	Weight Bearing	1125lb (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.18lb (82.4g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)



Ordering

Product Code	Series	Optics
P22	PV	
		CL = Clear
		FR = Frosted

Dimensions

