

P30 is a compact, walkover-rated fiber optic end fixture engineered for subtle and durable lighting in architectural and landscape installations. Constructed from 316 stainless steel, it features a 0.51" flat clear lens delivering a fixed 54° beam angle. Designed for recessed mounting, it supports fiber sizes from 0.08" to 0.31" and withstands loads up to 1,125 lbs. Weighing just 0.65 lbs, **P30** is lightweight yet built for lasting performance. With an IP65 rating and an operating temperature range of 14°F to 113°F, it delivers reliable, durable performance in both indoor and outdoor environments.

14°F to 113°F (-10°C to 45°C)

Walkover

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



IP65

Lighting	Beam Angle	54°
	Housing Construction	316 Stainless Steel, Tempered Glass
Mechanical	Optics	Ø0.51" (Ø13mm) Flat Clear Lens
	Weight Bearing	1125lbs (510kg)
	Mounting	Recessed
	Min/Max Fiber size	0.08" - 0.31" (2mm - 8mm)
	Weight	0.65lbs (29.3g)
Environmental	Ingress Protection	IP65
	Certifications	Made in USA
	Operating Temperature	14°F to 113°F (-10°C to 45°C)

Ordering

Product Code	Series	Optics
P30	PV	CL
		CL = Clear

Dimensions

