

# SP2020

BL Fixform

Indoor Suspended Aluminium Extrusion  
Designed for use with **BL Flexform** Series



SP2020 channel has a rounded 3/4" (20.2mm) cylindrical shaped profile optic, allowing you to design your own custom pendant luminaires. Conductive suspension wires combine structural with electrical to seamlessly energize the light, and are adjustable in height. Create linear pendants, custom hanging chandeliers and one-of-a-kind artistic lighting expressions.

**Quick Ship**

<b>CLIENT</b>	
<b>PROJECT NAME</b>	
<b>LOCATION</b>	
<b>DATE</b>	

## Product Detail




<b>Mechanical</b>	Housing Construction	Aluminum Enclosure Polycarbonate Optic (75% Trans.) Plastic End Caps
	Stock Length	6ft (1.83m)
	Minimum Cut Length	Based on BL Flexform Increments
<b>Components</b>	CH-SP2020-E	Aluminum Base Track
	LE-SP2020-E	Polycarbonate Optic
	EC-SP2020-E	Plastic End Cap
	WR-SP2020-E	Steel Suspension Wire
	HS-SP2020-E	Anodized Aluminium Hanger
<b>Environmental</b>	Ingress Protection	IP20
	Certifications	cULus

## Ordering

Product Code
SP2020-E-AL-FR-IP20

## Dimensions



Size	A	B	C	D	E	F
inch	0.45	0.79	0.69	72	0.69	0.48
mm	11.4	20	17.6	1829	17.6	12.2

Custom channel colors are available, please consult BL Lighting for more information.

### BL LIGHTING ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8  
P: 1-804-874-4405 E: info@blighting.com  
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at blighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

[blighting.com](http://blighting.com)

