

Side Select V Tunable

BL Select Neon

Diffused, Flexible, Linear LED Lighting,
24VDC, Constant Voltage, Vertical Bend,
Side Profile, Silicone, Tunable White



Side Select V Tunable features a fully flexible silicone encapsulated diffuser and is rated for -40°F to 131°F (-40°C to 55°C) with an IP68 waterproof rating for reliable performance in interior and semi-outdoor applications. Its vertical bending design allows adjustable warm-to-cool white light with delivering uniform, and dot-free illumination. Ideal for retail and hospitality interiors, accent walls, columns, or architectural features, it provides versatile lighting tones for professional, dynamic, and visually engaging installations.


Dot-free Seamless connections -40°F to 131°F (-40°C to 55°C) Tunable White

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	Lamp	LED, SMD 2835
	LED's Per Foot	37 LEDs/ft (120 LEDs/m)
	Beam Angle	120°
	Average Life	50,000 Hours
	CCT Binning	SDCM <3, One Step Binning
Electrical	Controls	0-10V, MLV, ELV, Phase-Cut, TRIAC, DMX, Bluetooth
	Input Voltage	24VDC
	Max Input Current	4.12A
	Connections	3x20AWG Wires
	Power Cable Length	Standard 10ft (3m). Also available in 16ft (5m)
Mechanical	Circuit	Class 2
	Housing Construction	Injection Moulded White Silicone
	Mounting	Mounting Clips, Mounting Channels
	Weight	0.31 lb/ft (0.46 kg/m)
	Dimensions	W: 0.65" x H: 0.65" (W: 16.5mm x H: 16.5mm)
Environmental	Minimum Bend Radius	2.36" (60mm)
	Operating Temperature	-40°F to 131°F (-40°C to 55°C)
	Ingress Protection	IP68
	Impact Protection	IK08
	Resistance	UV, Flame, Solvents, Saltwater and Dirt Resistant
	Certifications	UL, CE, RoHS Compliant, CB



Performance

CCT/Color		2200K + 5700K	2700K + 5700K	3000K + 5700K
Power	W/FT (W/m)	3.66 (12)		
Lumens	lm/FT (lm/m)	80.2+89.6 (263+294)	102+92.7 (333+304)	82.9+84.8 (272+278)
Efficacy	lm/W	22+25	28+25	23+23
CRI	CRI	80		
Increment	inch (mm)	3.94(100)		
Max. Length	ft (m)	26.6ft (8.1m)		

Ordering

Product Code	Series	CCT	Input Voltage	IP Rating
SVTN	SEN	2200K+5700K 2700K+5700K 3000K+5700K	24	IP68

Note:
Lengths, Lead Orientations & Mounting Accessories for BL Select Neon must be confirmed at time of order.

BL LIGHTING
ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information, please download the BL LIGHTING catalog

bllighting.com





Side Select V Tunable

BL Select Neon

Diffused, Flexible, Linear LED Lighting,
24VDC, Constant Voltage, Vertical Bend,
Side Profile, Silicone, Tunable White




Minimum Bend Radius and Bend Orientation



BL Neon Side Select V Series bends vertically

Horizontal bend option available on BL Select Neon Side Select H Series

Beam Angle & Viewing Angle




Average Beam Angle (50%), 3000K: 113.8°

Dimensions & Lead Orientations


Back Lead

SEN SL BC 68




End Lead

SEN SL EC 68




Right Side Lead

SEN SL RC 68



End Cap



**The Wick Resistant Wire Ferrule is built into the lead wire, 5.12" (130mm) from the BL Select Neon Series Termination Connection, for additional moisture ingress protection. Removal of the Wick Resistant Wire Ferrule may void your warranty.*

BL LIGHTING
ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-804-874-4405 E: info@bllighting.com
Copyright © BL INNOVATIVE LIGHTING. All Rights Reserved.

Solid State Lighting is sensitive to power fluctuations. Surge protection is highly recommended for all LED lighting products and should be on a dedicated circuit to protect against premature failure. Lack of surge protection may void your warranty.

Designed & Assembled in North America.

Specifications subject to change without notice. Please refer to our website at bllighting.com for current technical data.

For more information,
please download the
BL LIGHTING catalog

bllighting.com

