

When true incandescent is a must-have, the fully customizable Spotglobe INC Series string light is a highly flexible solution. Traditional, classic, and romantic. Incandescent lamps are suitable for higher ambient temperatures. Designed to meet a variety of potential applications and environments, such as restaurants, sun decks and alleyways. Festoon lights across landscapes, patio, and walkways; accent building outlines and add impact to signs.

-4°F to 104°F (-20°C to 40°C)

CLIENT	
PROJECT NAME	
LOCATION	
DATE	

Product Detail



Lighting	Lamp	Incandescent, Clear Optic
	Power	5W
	Average Life	10,000 Hours
	Lumens	28 lm/Lamp
	Efficacy	5.6 lm/W
Electrical	Controls	MLV Dimming
	Input Voltage	24VAC
	Max Input Current	5A, Maximum 18 Lamps per Series
	Connections	16AWG, Copper Conductors
Mechanical	Circuit	Class 2
	Housing Construction	UV Stabilized Polycarbonate Globe
	Base	E10
Environmental	Weight	0.049lb (22g)/ea
	Operating Temperature	-4°F to 104°F (-20°C to 40°C)
	Ingress Protection	IP65
	Mounting	Insulated Clip, Aircraft Cable
	Lamp Spacing	3", 4", 6", 9", 12", 18", 24"
Certifications	cULus, CE	

Ordering

Product Code	Series	Lamp Spacing	Input Voltage	IP Rating
SGINC	S		24	IP65
		03 = 3" o.c.		
		04 = 4" o.c.		
		06 = 6" o.c.		
		09 = 9" o.c.		
		12 = 12" o.c.		
		18 = 18" o.c.		
		24 = 24" o.c.		

Max. Length

3" o.c.	4.5ft
4" o.c.	6ft
6" o.c.	9ft
9" o.c.	13ft
12" o.c.	18ft
18" o.c.	27ft
24" o.c.	36ft

Dimensions

